



SCRUBBER DRIERS - WALK BEHIND

# CT90

MAX PRODUCTIVITY

3825 m<sup>2</sup>/h

BATTERIES  
RUNNING TIME

4 h

WATER TANK  
RUNNING TIME

80 min  
working session



## INNOVATIONS



DBL™  
DOUBLE  
BATTERY  
LIFE



SLST™  
SELF  
LEVELING  
SYSTEM

## SPECS



INTUITIVE CONTROL PANEL



"V"-SHAPED SQUEEGEE

## MOST FREQUENTLY USED



RETAIL



HOSPITALITY



BUILDING SERVICE CONTRACTORS



MUNICIPALITIES



## TECHNICAL DATA

CT90 BT70

Code	
<b>PERFORMANCE</b>	
Max theoretical productivity	3150 m <sup>2</sup> /h
Cleaning path	700 mm
Water tank capacity (solution recovery)	85/90 l
Max running time	270 min
Voltage	24(4x6) - 180 GEL V-Ah
Installed power	1440 W
Brush pressure	31,4 kg
Squeegee width	942 mm
Max speed	4,2 km/h
Weight	98,4 kg
Dimension (LxWxH)	1328 x 748 x 1025 mm

## CONSUMABLES (Codes available on price list)

### BRUSHES



SPPV01472 | POLYPROPYLENE (PP) BRUSH

### PADS



L-222324 | 14' POLISH PAD - WHITE  
 L-222325 | 14' BUFF PAD - RED  
 L-222326 | 14' SCRUB PAD - BLUE  
 L-222327 | 14' STRIPPING PAD - BROWN  
 L-1243354 | 14' BUFF PAD - RED (BOX OF 5)

### SQUEEGEE BLADES



MPVR08040 | LATEX FRONT BLADE  
 MPVR08036 | LATEX REAR BLADE

IPC Australia  
 Unit 11, 4 Southridge Street  
 Eastern Creek NSW 2766

T: 1800 226 843 (FREE CALL)  
 T: +61 2 9839 9700

E: [contactanz@ipcworldwide.com](mailto:contactanz@ipcworldwide.com)  
 W: [www.ipcworldwide.com](http://www.ipcworldwide.com)

IPC New Zealand  
 Unit 5, 103 Cryers Road  
 East Tamaki  
 Auckland 2013

T: +64 9 253 9013  
 F: +64 9 253 9015